



TAMBURO 16

120V PENDANTS

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

Cable-hung or stem-mount pendant with handcrafted glass diffuser.

LAMPING

Standard: 3x100W A19 120V incandescent, lamp not included. Dimmable with standard incandescent dimmer (not included).

LED: 11W Replaceable source, 120V, dimmable, 90+ CRI, 3000°K CCT, 1100 lumens, 30,000 hours. Lamp included.

DIFFUSER

Shades shall be handcrafted glass in various decors. Includes frosted glass glare shield. 15.75" Dia. x 7.875" H

Opening sizes: 3x7mm holes.

SUSPENSION

Cable-hung: 3x 10' aircraft-quality stainless steel cable support with 10' AWM-type cord. Jacket tint coordinates with metal finish. 5" Dia. canopy is plated stamped steel. Bronze or Satin Nickel.

Stem-mount: 4 connectable stem sections (3", 6", 12" and 18" lengths) plus telescoping piece for up to 3" adjustment, 10' max. 5" Dia. canopy (with swivel) and stem sections are plated steel. Bronze or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal ceiling box. Suitable for sloped ceilings.


LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).

Consult factory concerning lower wattage labeling for energy requirements.



TAMBURO 16 SHOWN IN CLEAR STONE (400800) & GLITTER STONE (4008GL)



For ordering information, see next page

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 12/18




ORDERING:

CONNECTION	SHADE OPTIONS	LAMP OPTIONS	METAL FINISH	OPTIONS
3x Cable Fixture	400807 Opal Matte	(blank) 3x 100W A19 Incan	BR Bronze	L 15' cord
1KV 1 Lt. Flat	4008CH Cherry 4008KR Chalk	LED 3x 11W LED 120V, dimmable	SN Satin Nickel	LW Low wattage labeling
Stem Fixture	40080K Oak			
1KT 1 Lt. Flat	4008TN Titan 400800 Clear Stone 4008CS Stone Copper Foil 4008GL Glitter Stone 4008GS Stone Gold Foil 4008SS Stone Silver Foil			

Ex. 1KV-40080K-SN
Tamburo 16 Pendant w/ Oak Glass,
Satin Nickel Finish


PENDANT OPTIONS:

CABLE-HUNG PENDANT



- 3x 10' aircraft-quality stainless steel cable
- 1KV Series: 3x lampholder includes flat glass glare shield
- Cord: 10' AWM-type provided
- Bronze or Satin Nickel

STEM PENDANT



- Swivel at canopy, suitable for sloped ceilings
- Includes telescoping section plus 4 connectable stem sections, (1x 3", 1x 6", 1x 12", 1x 18"), 10' max
- Bronze or Satin Nickel

ACCESSORIES:

ADDITIONAL STEM SECTIONS:

Additional connecting stems are available to increase overall length, up to 10' max. Telescoping adjustable section allows up to 3" movement.

- T20A-SN** or **T20A-BR** Adj. Section
- T203-SN** or **T203-BR** 3" Section
- T206-SN** or **T206-BR** 6" Section
- T212-SN** or **T212-BR** 12" Section
- T218-SN** or **T218-BR** 18" Section

Project Information: